



Optical Laser Source

BOU350

- ◆ 1~3 wavelengths output from one port
- ◆ High stabilization, built-in optic isolator
- ◆ 270Hz, 1KHz, 2KHz modulation output
- ◆ Energy save mode
- ◆ Auto-Wave ID output, work with TriBrer OPMBOU350
- ◆ One-year warranty and Three-year recommended calibration interval



CE
FDA

Standard



Carrying bag



Calibration certificate



Manual



Packing box

Optional



AC/DC adapter



NEXT-Generation
Network Measurement



ISO9001



ISO14001:2015

SPECIFICATIONS

Model	M8	M3	S3	S4	S5
Wavelength(nm)	850	1300	1310	1490	1550
Stabilization*	±0.05dB / 1 hour; ±0.1dB / 8 hours				
Output Power	> - 6dBm @ 1310nm/1490nm/1550nm/1625nm / > -10 dBm @ 850nm/1300nm				
Modulation	270Hz, 1KHz, 2KHz				
Connector	FC/PC (or customize)				
Auto Power Off	No operation in 10 minutes (can be canceled), Low battery energy				
Battery Charge	Yes				
Power Supply	AA * 2 batteries or AC/DC power supply adapter				

* After 5 minutes warm-up, 20±3°C, CW, FC connector, with optic isolator

GENERAL SPECIFICATIONS

Size(H*W*D)	160mm * 75mm * 32mm
Weight	About 180g
Storage Temperature	-20 -- +60 °C, < 90%RH
Operating Temperature	-10 -- +50 °C, < 90%RH

ORDERING INFORMATION

BOU350-X

Model

BOU350-M3M8 = 850/1300nm

BOU350-S3S5 = 1310/1550nm

BOU350-S3S4S5 = 1310/1490/1550nm