

Programmable DC Electronic Load

—150W-200W-300W Series



OVERVIEW

- HT8XXX load is a precision programmable DC electronic load controlled by a high-performance microprocessor. It uses 3.5-inch TFT true color LCD display with Chinese and English menu.
- Offers 4 basic working modes (CC/CV/CR/CW) and 10 functional modes.
- With comprehensive protection, over-heat protection, over-current protection, over-power protection, over-voltage protection, loop oscillation protection. HT8XXX series E-load supports RS232, LAN, USB and analog interfaces to fit your versatile solution and testing needs.



4 basic working modes CC/CV/CR/CW and 11 functional modes multiple extended function modes:

- Short test function
- DYNA dynamic test function
- OCP over current protection mode
- BATT battery mode
- EFFT load effect mode
- SWEEP dynamic frequency conversion scanning function
- TIMEING_me measurement function
- OVP over voltage protection mode
- AUTO mode
- LIST function
- LED (HP8151 has no LED mode)

特性 (FEATURES)

- 500kHz high speed voltage, current sampling rate
- High precision voltage and current measurement
- Fast loop response speed and current slew rate
- Programmable single step up to 10 μ S
- Equipped with remote four-wire compensation
- Unique real-time display of current ripple and voltage ripple
- Real-time display of load power and resistance

应用 (APPLICATION)



SPECIFICATION

Model	HT8151		HT8151A		HT8151B		HT8201	
Input voltage	15V	150V	15V	150V	50V	500V	15V	150V
Input current	3A	30A	3A	30A	1.5A	15A	3A	30A
Input power	150W						200W	
Min.operation voltage	1.5V@30A				7.5V@15A		1.5V@30A	
Min.rise time@FS current	10us							
CV mode								
Range	15V	150V	15V	150V	50V	500V	15V	150V
Resolution	0.2mV	2m	0.2mV	2mV	0.7mV	7mV	0.2mV	2mV
Accuracy	±(0.05%+0.025%FS)							
CC mode								
Range	3A	30A	3A	30A	1.5A	15A	3A	30A
Resolution	0.04mA	0.4mA	0.04mA	0.4mA	0.02mA	0.2mA	0.04mA	0.4mA
Accuracy	±(0.05%+0.05%FS)							
CR mode								
Range	0.1Ω~7.5kΩ		0.1Ω~7.5kΩ		0.1Ω~7.5kΩ		0.1Ω~7.5kΩ	
Resolution	16Bits							
Accuracy	±0.1%							
CW mode								
Range	150W						200W	
Resolution	16Bits							
Accuracy	± (0.1%+0.1%FS)							
LED mode								
bandwidth	-----		100kHz以上					
Rd coefficient	-----		0.001~1					
Dynamic mode								
Ta&Tb	10uS~50s							
Min.resolution	10us							
Min. rise time	1.5A/us		1.5A/us		0.8A/us		1.5A/us	
Read-back voltage								
Range	15V	150V	15V	150V	50V	500V	15V	150V
Resolution	0.1mV	1mV	0.1mV	1mV	0.3mV	3mV	0.1mV	1mV
Accuracy	±(0.025%+0.025%FS)							
Read-back current								
Range	3A	30A	3A	30A	1.5A	15A	3A	30A
Resolution	0.02mA	0.2mA	0.02mA	0.2mA	0.01mA	0.1mA	0.02mA	0.2mA
Accuracy	±(0.05%+0.05%FS)							
Read-back Ripple								
Range(R/I)	-----		150V/30A		500V/15A		150V/30A	
bandwidth	-----		10Hz~250kHz					
Accuracy	±1%							
Protection range								
Over-power protection	158W						210W	
Over-current protection	32A				16A			
Over-voltage protection	158V				525V			
Over-temperature protection	≈85℃							
Specification								
Dimension (D*W*H)	358mm*214mm*88mm							
Gross Weight	3.8Kg							