

No.	Item	Parameter	Index				
1	OUT PUT	DC output voltage	+12V				
2		DC voltage adjustable range	0-12V				
3		Output voltage tolerance	±2%				
4		Rated output current	200A				
5		Output current range	0-200A				
6		DC output power	2500W				
7		Work efficiency	88%				
8		Ripple and noise	≤480mVp-p				
9		Line voltage stability	±0.5%				
10		Load stability	±0.5%				
11	IN PUT	Input voltage range	190-250VAC;47-63HZ; 280-370VDC				
12		AC input current	15A/230VAC				
13		electric shock	230VAC/50A				
14		Leakage current	<1mA/240VAC				
17		Temperature Coefficient	±0.03%/°C(0~50°C)				
19		Start, rise, hold time	1s,50ms,60ms/230VAC				
20		Pressure resistance	IN PUT -OUT PUT 1KV				
21			IN PUT - SHELL 1KV				
22	OUT PUT - SHELL 0.5KV						
24	Working temperature	Working temperature, humidity	-20~50°C;20%-90%RH				
25		Storage temperature, humidity	-20+85°C;10%~95%RH				
26	protection	Overload protection	105-150%				
27		Overvoltage protection	17.5V				
28		Over temperature protection	85°C				
29		Size	280*185*68				
		KG	4.8kg				
			S-2500-12				
				部门			
				技术部			
标记	处数	更改文件号	签名	日期	阶段标记	第 1 页	WENZHOU FUNI ELECTRICAL CO.,LTD
设计		标准化				共 1 页	
校对		日期	18.11.22				

