


Soldering Hints

- Put leads through mounting holes from the side with part outline. Ensure component evenly touch PCB.
- Solder leads at the other side. Solder should fully fill and cover soldering pads. Avoid bridges between neighboring pads.
- Cut unused leads flush with cutter.



DSO 138 Oscilloscope DIY Kit

User Manual

Rev. 05 Applicable models: 13803K, 13804K
Applicable firmware: 113-13801-060 or later

Tools you need

- Iron (20W)
- Solder wire
- Multimeter
- Screw driver
- Flush cutter
- Tweezers

Before you start

- Check part values & quantities against part list
- Always meter resistor values before soldering
- Understand all part polarities and orientations


Important !!!

Install all SMD parts before proceeding to Step1 if you purchased kit 13804K.

Step 1

Assembly Main Board and LCD board (follow the order as numbered)

1. Resistors



Note:
Always meter resistor values before soldering

- R1, R14, R16 : 100K Ω
- R2 : 1.8M Ω
- R3 : 200K Ω
- R4 : 2M Ω
- R5 : 20K Ω
- R6 : 300 Ω
- R7, R36 : 180 Ω
- R8, R12, R13 : 120 Ω
- R9, R15, R26 : 1K Ω
- R10 : 3K Ω
- R11 : 150 Ω
- R38 : 1.5K Ω
- R28, R40 : 470 Ω
- R37, R39 : 10K Ω

2. HF-Chokes



- L1, L3, L4 : 100 μ H

3. Diodes



Cathode


- D1 : 1N5819
- D2 : 1N4004 (or 1N4007)

4. Crystal



- Y1 : 8MHz

5. USB Socket *



- J4 : USB mini -B

Note:
This connector is optional.

6. Tact Switches



- SW4, SW5 : 6 X 6 X 5mm
- SW6, SW7, SW8

7. Ceramic Capacitors



- C1, C9, C10, C11, C14, C15, C16, C17, C18, C20, C23 : 0.1 μ F
- C2 : 330pF
- C3 : 3pF
- C5 : 1pF
- C7, C8 : 120pF
- C12, C13 : 22pF

8. LED



Solder positive pole (the longer lead) to the square pad



- D3 : ϕ 3mm, green

9. Pin header (for power)



Face the opening outward

- J9 : 2 Pin

10. Transistors



- Q1 : 8550
- Q2 : 9014

Attention!
Packages are similar. Do not mix up!

11. Regulators



- U4 : 79L05
- U5 : 78L05

Attention!
Packages are similar. Do not mix up!

12. Capacitor trimmers



- C4, C6 : 5 - 30pF

13. Power inductor



- L2 : 1mH/0.5A

14. Electrolytic capacitors




Solder positive pole (the longer lead) to the square pad



- C19, C21, C22, C24, C25, C26 : 100 μ F/16V

15. Power connector



- J10 : DC005

16. Pin-header (male) *



- J5 : 1 X 3 pin
- J6 : 1 X 4 pin

Note:
These pin-headers are optional.

17. Pin-header (female)



- J7, J8 : 1 X 2 pin
- J3 : 2 X 20 pin

18. Slide switches



- SW1, SW2, SW3 : 2P3T

19. BNC connector



- J1 : BNC

Note:
The thicker pins need to heat up longer to get good soldering result.

20. Test signal ring



- 1) Make a small ring with a lead cut-off.
- 2) Solder the ring to the two holes of J2 (as shown in the photo).

21. JP3



Short JP3 with solder

22. LCD Board



Note: Install to the side opposite to LCD panel.

- J1 : 2 X 20 pin
- J2, J3 : 1 X 2 pin

Finished look




Step 2 Test and Use

- Notes:**
- 1) JP1, JP2, JP5, and JP6 at bottom side should be kept open for normal running mode.
 - 2) The USB connector do not have function. It was provided for future or user own use.
 - 3) A 9V DC power supply (> 200mA capacity) is required to run the scope. Power supply is not included in the kit.

A. Check voltages

- 1) Apply 9V power to J10 (or J9).
- 2) Check voltage at TP22. It should be around +3.3V.
- 3) If voltage at TP22 is good disconnect power. Short JP4 with solder permanently.



B. Attach LCD board

Plug LCD board into the female headers J3, J7, and J8 on the main board.



C. Verify


- 1) Connect power supply again. You should see LCD lights up and oscilloscope panel displayed.
- 2) Press various buttons and move switches to verify their functions.




"Trigger" LED blinking twice indicates booting-up is good.

A. Use

- 1) Attach probe clips to J1.
- 2) Touch the red clip with your finger. Do you see signal from your finger?



Troubleshooting



NOTE 2:
LED will be blinking constantly if MCU (U1) can not detect valid LCD controller. Check LCD pin-header soldering.

NOTE 1: The voltages in the photo are for reference only. The voltages on your board could be different. But they should be close to the values shown.

NOTE 3:
Make sure U1 and LED working (you see LED blinks twice at pressing RESET) before using Test Mode.


Test Mode

What it is and how it works

Test Mode is used to find out possible opens (for all port pins) and shorts (for pins PB0 - 15 and PC13-15). When entered it first checks PB and PC pins with special patterns to find out possible shorts. If found LED will be fast blinking. Otherwise, it generate 3.3V and 0V alternatively at each port pins (PA, PB, PC and PD) in cycle of about 4 seconds. These signals can be used to check for opens.

How to use

1. Hold down SW4 and press RESET to enter Test Mode.
2. If you see LED fast blinking that means there are shorts on PB or PC pins. You need to find out the shorts first.
3. If you see LED slowly blinking use a volt-meter to check each pin related connections that are suspected open. When you don't see voltage change at a spot which is supposed being connected to a port pin there may be open between the spot and the port pin.




Voltage References

Place the negative pen of volt-meter here to do voltage measurements.

NOTES:
*: These voltages are input voltage dependent. The values shown were measured when input voltage was 9.39V.
**: These voltages are measured when CPL switch (SW1) is set to GND position.

How to Use

Display and Controls



Connections

Power Supply: Connect DC power supply to J9 or J10. The power supply voltage must be in the range of 8 - 12V.

Probe: Connect probe to J1.

Attention

1. Power supply voltage must not exceed 12V. Otherwise U5 will get hot.
2. Allowed maximum signal input voltage is 50Vpk (100Vpp) with the clip probe.

Operations

- Press on [SEL] button:** Select parameter to be adjusted. The selected parameter will be highlighted.
- Press on [+] or [-] button:** Adjust the parameter selected by [SEL] button.
- Press on [OK] button:** Freeze waveform refresh (entering HOLD state). Press on it again will de-freeze.
- Change [CPL] switch:** Set couple to DC, AC, or GND. When GND is selected the scope input is isolated from input signal and connected to ground (0V input).
- Change [SEN1] or [SEN2] switch:** Adjust sensitivity. The product of [SEN1] and [SEN2] settings makes the actual sensitivity which is displayed at the lower-left corner of the panel.
- Press on [Reset] button:** Perform a system reset and re-boots the oscilloscope.

Tips

Vpos Alignment

This is to fix the mismatch between 0V trace and VPos indicator. To do this set couple switch [CPL] to GND position. Press on [SEL] button to make VPos indicator highlighted. Hold down [OK] button for about 2 seconds. You will see VPos indicator aligned to 0V trace when you release [OK] button. You may see some residue mismatch remains at the highest sensitivity settings. This is normal.

Restore Factory Default

Hold down [+] and [-] buttons simultaneously for 2 seconds.

Auto-center Trigger Level

Highlight trigger level indicator and hold down [OK] button for 2 seconds.



Auto-center Horizontal Position

Highlight HPos indicator and hold down [OK] button for 2 seconds.


Probe Calibration

Because there is always some capacitance between scope input and ground probe needs to be calibrated to achieve better measurement results for high frequency signals. This can be done with the help of the built-in test signal. To do this please follow the steps below.


1. Connect the red clip to the test signal terminal and leave the black clip un-connected (see photo at right).
2. Set [SEN1] switch to 0.1V and [SEN2] switch to X5. Set [CPL] switch to AC or DC.
3. Adjust timebase to 0.2ms. You should see waveform similar to that shown in photos below. If traces are not stable adjust trigger level (the pink triangle on right screen border) so as you get a stable display.
4. Turn C4 (capacitor trimmer) with a small screw driver so that the waveform displays sharp rightangle (photo C).
5. Set [SEN1] switch to 1V and [SEN2] switch to X1 while keep all other settings unchanged. Adjust C6 so that sharp rightangle waveform is displayed.



A - Not enough



B - Too much



C - Good

Turn On/Off Readouts

Press [SEL] so that timebase is highlighted. Hold down [OK] button for about 2 seconds. This will turn on/off measurement readouts.

Waveform Save/Recall

Press [SEL] & [+] simultaneously: Save currently displayed waveform to non-volatile memory.
Press [SEL] & [-] simultaneously: Recall saved waveform

Triggers and Their Modes

Triggers are events that indicate signal voltage crossing a set level (i.e. trigger level) along a specified direction (i.e. trigger slope, rising or falling). Oscilloscope uses triggers as reference points in time for stable waveform display and measurements.

Auto Mode

In auto mode oscilloscope will perform display refresh no matter triggers happen or not. When triggers are detected waveform display will be displayed with reference to trigger points. Otherwise, display waveform at random reference points.

Normal Mode


In normal mode oscilloscope will only perform display refresh when there are triggers. If no triggers happen waveform display will stay unchanged.

Single Mode

Single mode is the same as normal mode except that oscilloscope will enter HOLD state after a trigger has been detected and waveform display has been updated.

Normal and single modes are useful for capturing sparse or single waveform.

Specifications	
Max realtime sample rate	1MSa/s
Analog bandwidth	0 - 200KHz
Sensitivity range	10mV/div - 5V/div
Max input voltage	50Vpk (1X probe)
Input impedance	1M ohm/20pF
Resolution	12 bits
Record length	1024 points
Timebase range	500s/Div -- 10us/Div
Trigger modes	Auto, Normal, and Single
Trigger position range	50%
Power supply	9V DC (8 - 12V)
Current consumption	~120mA
Dimension	117 x 76 x 15mm
Weight	70 gram (without probe)



MCU

ADCIN	10	PA0
VSENSEL2	11	PA1
VSENSEL1	12	PA2
CPLSEL	13	PA3
TP11	14	PA4
TP12	15	PA5
TP13	16	PA6
TRIG	17	PA7
TX1	29	PA8
RX1	30	PA9
USBDM	31	PA10
USBDP	32	PA11
SWDIO	33	PA12
SWCLK	34	PA13
LED	37	PA14
LED	38	PA15
DB0	18	PB0
DB1	19	PB1
DB2	20	PB2
DB3	39	PB3
DB4	40	PB4
DB5	41	PB5
DB6	42	PB6
DB7	43	PB7
TL_PWM	45	PB8
VGEN	46	PB9
LCD_nRD	21	PB10
LCD_nRESET	22	PB11
BTN4	25	PB12
BTN3	26	PB13
BTN2	27	PB14
BTN1	28	PB15
LCD_nCS	2	PC13/TEMPER/RTC
LCD_RS	3	PC14/OSC32_IN
LCD_nWR	4	PC15/OSC32_OUT
		VSS_1
		VSS_2
		VSS_3
		VDD_1
		VDD_2
		VDD_3
		VDD_4
		VDD_5
		VDD_6
		VDD_7
		VDD_8
		VDD_9
		VDD_10
		VDD_11
		VDD_12
		VDD_13
		VDD_14
		VDD_15
		VDD_16
		VDD_17
		VDD_18
		VDD_19
		VDD_20
		VDD_21
		VDD_22
		VDD_23
		VDD_24
		VDD_25
		VDD_26
		VDD_27
		VDD_28
		VDD_29
		VDD_30
		VDD_31
		VDD_32
		VDD_33
		VDD_34
		VDD_35
		VDD_36
		VDD_37
		VDD_38
		VDD_39
		VDD_40
		VDD_41
		VDD_42
		VDD_43
		VDD_44
		VDD_45
		VDD_46
		VDD_47
		VDD_48

Analog Channel

USB

Uart

Buttons

Test Signal Terminal

SWD Port

LCD Module Connector

Power Supply

Caution:
Power supply voltage can not be higher than 12V.

Notes:

1. Part values used could be different to the values shown. Please refer to part list.
2. Parts in dash-line boxes are SMD devices.