

Optical Power Meter-----JW3211 Series

JW3211 optical power meter

Is a handheld optical power meter, newly released in 2007, which can be used for absolute optical power measurements as well as for relative loss measurements in optic fiber networks. An Ø1.0mm photosensitive area photodiode is used to significantly improve the stability and the reliability. It features ingenious appearance, wide range of power measurement, high accuracy, user self-calibration function and reference power level storage.

Features

- Wide dynamic measurement range (**up to 80dB**)
- Reference power level storage(**Ref Setting**)
- User self-calibration function
- Comfortable LCD display and backlight LCD display supports night operation.
- Power measurements in dBm or mw and insertion loss in dB
- 10 minutes Auto-off function can be activated or deactivated.
- AA alkaline batteries can last more than 140 hours, AC adaptor also available
- Low battery indication



Applications

Telecom Maintenance
CATV Maintenance
Fiber Optic lab testing
Other Fiber Optic Measurements

Specifications

MODEL	JW3211A	JW3211C
Wavelength(nm)	800~1700nm	
Detector Type	InGaAs	
Detector Size	Ø 1.0mm	
Measurement Range (dBm)	-70~+10	-50~+30
Uncertainty	±5%	
Calibrated Wavelength(nm)	850,1300,1310,1490,1550,1625	
Resolution(dB)	0.01	
Optical Connector	FC(interchangeable SC,ST) / as well as 2.5mm universal	
Power Supply	Alkaline Battery(3 AA 1.5V batteries); AC Adaptor(9V)	
Battery Operating Time	140 h with 1.5V Battery(3pcs)	
Operating Temperature(°C)	-10 ~ +60	
Storage Temperature(°C)	-25 ~ +70	
Relative Humidity	0 to 95% (non-condensing)	
Dimension(mm)	190X100X50	
Weight(g)	370	

Standard Packages

MODEL	INCLUDES
All JW3211 Models	JW3211 Optical Power Meter, 3pcs 1.5V batteries, AC Adaptor, User Manual, Cotton Sticks and Soft carrying case.