Подключение адаптера OBDII через WIFI

Шаг 1:

Установите приложение для работы с адаптером.

Если у Вас смартфон на базе Android, установите приложение TORQUE или DashCommand из Google Play.



Если у Bac Iphone или Ipad, найдите в App Store приложение DashCommand и установите его.



Шаг 2:

Найдите в автомобиле разъём OBDII и подключите к нему адаптер. Индикатор питания адаптера начнет мигать. Далее устройство перейдёт в режим ожидания.

Подключение адаптера OBDII через WIFI

Шаг 1:

Установите приложение для работы с адаптером.

Если у Вас смартфон на базе Android, установите приложение TORQUE или DashCommand из Google Play.



Если у Bac Iphone или Ipad, найдите в App Store приложение DashCommand и установите его.



Шаг 2:

Найдите в автомобиле разъём OBDII и подключите к нему адаптер. Индикатор питания адаптера начнет мигать. Далее устройство перейдёт в режим ожидания.

Шаг 3:

На смартфоне зайдите в меню «Настройки», включите Wi-Fi, выполните поиск новых устройств и подключитесь к устройству «KONNWEI WIFI».

А. Запустите приложение Torque б. Выберите раздел «Adapter Status» (Настройки адаптера).

В. Выберите пункт «Connection to adapter» (Тип подключения).

Д. Выберите тип подключения «Wi-Fi» е. Перезапустите приложение Torque.

*DashCommand выполнит подключение автоматически.



Шаг 3:

На смартфоне зайдите в меню «Настройки», включите Wi-Fi, выполните поиск новых устройств и подключитесь к устройству «KONNWEI WIFI».

A. Запустите приложение Torqueб. Выберите раздел «Adapter Status»

(Настройки адаптера). В. Выберите пункт «Connection to adapter»

(Тип подключения).

Д. Выберите тип подключения «Wi-Fi»

e. Перезапустите приложение Torque.

*DashCommand выполнит подключение автоматически.



Подключение на Android

	\$ \$ \$ \$ 0 -
WLAN	•
CONNECTED	
KONNWEI WIFI Connected, no Internet	(10
JWHX Saved	£ \$
AVAILABLE NETWORKS	
360WiFi-7952	
Bonstyle	1 © 0
ChinaNet-gulb	₽ (¥)
ChinaNet-nCdZ	
ChinaNet-t7X2	₽ † <u>(</u>)
Q	

Подключение на Android

< WLAN				
WLAN				
CONNECTED				
KONNWEI WIFI Connected, no Interne	it		((0-	
JWHX Saved		8	((c-	
AVAILABLE NETWO	RKS			
360WiFi-7952		8	(t-	
Bonstyle		8	((:-	
ChinaNet-gulb		8	0	
ChinaNet-nCdZ		8	(1-	
ChinaNet-t7X2		8	(t-	
	0			
	10 (A) (A)			



Engine Man	DRG	UE nostics and To Homis Nor Setu	ols
	Test	Map View	
	Result		7
Gra	pphing	1 0.8 Acce 0.0	-1





	Подключение на	IOS							
1:41 PM © \$ \$ \$ \$		6:53 PM 🛞	• =		mand	1	ach Comm	nand	
Adapter Status Information	: < Settings	WLAN							
Connection to adapter			2	2003 Audi A4I 2.5		2003 Audi A4I 2.5		2.5	
Are you connected to the OBD2 adapter? Yes - Connected to: WI-FI	WLAN		Oper	ning OBD-II Conne	ection	TUESDA	Y AUG 30, 2016 /	1:45 PM	80
Connection to ECU Can the adapter talk OK to the vehicle ECU?	KONNWEI W	'IFI 🤶	() OSHBOARDS	GAUGES	PERFORMANCE	DASHBOARDS	GAUGES		40
Adapter Frror Count	CHOOSE A NETWOR	K 3							20
This should stay on 0, if not then you potentially have a faulty adapter.	Bonstyle	ê ç		Q			Ğ		
Adapter Manufacturer	JWHX	€ ?	DATA GRID	DIAGNOSTICS	VEHICLE	DATA GRID	DIAGNOSTICS	VEHICLE	1/4
Who made the OBD2 adapter OBDII to R\$232 Interpreter	Wewom_Tian	nwei 🔒 🤶							1000
Adapter Version	Wi-Ferver-S2	Z 🔒 🗢	SKID PAD		INCLINOMETER	SKID PAD		NCLINOMETER	1/8 mile
The firmware version of the adapter ELM327 v1.5	Other		-	CONNECTING			CONNECTED	-	330 feet
Adapter Notes			RACE TRACK		SETTINGS	RACE TRACK		SETTINGS	60 feet
Cheap clone versions of this adapter (mostly found v Amazon/eBay) may not function with protocol J1850	Ask to Join Netw	vorks					- 50-		
PWM(Ford/other), and also may have issues with corrupted communications (resulting in pausing dial	S Known networks will	be ioined automatical	CONSOL	E	ACCOUNT	CONSOLI	а — А	CCOUNT	1/4 MI 0-60
1:41 PM 💿 🛊 🕸 👁 🖸		6:53 PM 🛞	• =-						×.
Adapter Status Information	: < Settings	WLAN		comi	nand			ano	<u> </u>
Connection to adapter			2	2003 Audi A4I	2.5	2	003 Audi A4I 2	2.5	
Are you connected to the OBD2 adapter?	WLAN		Oper	ning OBD-II Conne	ection	TUESDA	Y AUG 30, 2016 /	1:45 PM	80
Connection to ECU	KONNWEI W	IFI 🔶		~	87	\odot	~	(87	E 40
Can the adapter talk OK to the vehicle ECU?			DASHBOARDS	GAUGES	PERFORMANCE	DASHBOARDS	GAUGES F	PERFORMANCE	20
Adapter Error Count	CHOOSE A NETWOR	K 🖏	C OF					=	E.
This should stay on 0, if not then you potentially have a faulty adapter.	Bonstyle	07		5	A		15	A	
Adapter Manufacturer	JWHX	- G + ?	DATA GRID	DIAGNOSTICS	VEHICLE	DATA GRID	DIAGNOSTICS	VEHICLE	1/4
Who made the OBD2 adapter OBDII to RS232 Interpreter	Wewom_Tian	nwei 💦 🔒 🤝						E	mile 1000
Adapter Version	Wi-Ferver-S2	Z 8 🕫	SKID PAD		INCLINOMETER	SKID PAD		NCLINOMETER	1/8
The firmware version of the adapter ELM327 v1.5	Other			CONNECTING			CONNECTED		330
Adapter Notes			RACE TRACK		SETTINGS	RACE TRACK		SETTINGS	60 feet
Information about the OBD2 adapter Cheap clone versions of this adapter (mostly found v Amazon/eBay) may not function with protocol J1850 PWM(Ford/other), and also may have issues with	Ask to Join Netw	vorks	CONSOL		ACCOUNT	CONSOLE		CCOUNT	1/4 MI 0-60

ed communications (resulting in pausing dials Known networks will be joined automatically. If





QR-коды на скачивание программного обеспечения